

Direct Oil Pad

		
Lightweight Pads (200 pack) 502/01002	Lightweight Pads (50 pack) 502/01003	Heavyweight Pads (100 pack) 502/01004

Oil absorbents absorb hydrocarbons, diesel, petrol, oil-based paints, solvents, and other organic liquids e.g., chlorinated solvents, alcohol, antifreeze etc, they repel water, picking up only hydrocarbons.

Suitable for use inside and outside on land or water.

Direct oil absorbents are the easiest way to deal with small or large spills.

The quality of our absorbents is tested according to British Standard BS7959-2:2000

High strength even when fully saturated.

The hydrophobic nature repels water and absorbs oil.

Supplied in plastic packs for damp areas.

Suitable for use:-

- ◆ **Indoor use**
- ◆ **Outdoor use**
- ◆ **Settling ponds**
- ◆ **Waste-water lagoons**
- ◆ **Garage**
- ◆ **Fuel depot**

Compatibility	Water-repellency exceeds requirements of BS 7959-2:2000. May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc. Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
Fire resistance	Good. (Physically flame-retardant) Incinerable to zero ash.
Disposal	Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
Safety data	This product is non-toxic to users and to aquatic life. Further technical advice is available if required.
Note	All weights, dimensions, and other figures quoted are approximate

SKU	Weight / class	Colour	Weight (GSM)	Pad Size	Absorbency (litre)	Pads per pack	Pack weight kgs	Polypropylene content Meltblown	Ultrasonically bonded	Spun bonded on one side
502/01001	Light	Blue	175	40 x 52 cm	75 - 100	100	3.8	>99.5%	✗	✗
502/01002	Light	Blue	175	40 x 52 cm	150 - 200	200	7.5	>99.5%	✗	✗
502/01003	Light	Blue	175	40 x 52 cm	38 - 50	50	2	>99.5%	✗	✗
502/01008/w	Light	White	175	40 x 52 cm	150 - 200	200	7.5	100%	✗	✗
502/01009/w	Medium	White	240	40 x 50 cm	78 - 100	100	5.0	100%	✓	✗
502/01007	Medium	Blue	240	40 x 52 cm	104 - 139	100	5.2	>99.5%	✗	✗
502/01013/w-24	Medium	White	240	40 x 50 cm	88 - 100	100	4.8	100%	✓	✓
502/01013/w-30	Heavy	White	300	40 x 50 cm	97 - 125	100	6.0	100%	✓	✓
502/01004	Ultra	Blue	350	40 x 52 cm	150 - 200	100	7.5	>99.5%	✗	✗

Ultrasonically bonded reduces linting and improves tensile strength
 Laminated spunbond layer on one side improves tensile strength and tear resistance

Revision Date 18/10/2024