

Direct Antistatic Oil Pad



Our antistatic range of absorbent pads are manufactured from 100% meltblown polypropylene for maximum absorbent capacity and retention with rapid capillary action.

Each roll absorbs highly flammable liquids with no charge build up. Absorbs oil only, not water.

The heavier weight pad is ultrasonically bonded to provide

extra strength and greater absorbency. Ideal for use where flammable vapours are present.

Safely dissipates static electricity.

Suitable for

- Indoor use
- Laboratories
- Process plants
- Households

SKU Code	Pad Size	Weight (GSM)	Pack Quantity	Absorbency Litres Min - Max	Pack weight kgs
502/01013/AW	40 x 50cm	240	100	83 - 111	4.8
502/01005/AW	40 x 50cm	175	200	138 - 185	7.0

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

Composition:	>99.5% Polypropylene <0.5% antistatic additive Meltblown Ultrasonically bonded	>99.5% Polypropylene <0.5% antistatic additive Meltblown
Basis Weight	240 gsm	175gsm
Pack type:	Bag	Bag
Pack size:	50 x 40 x 27 cm	40 x 50 x 40 cm
Compatibility:	Water-repellency exceeds requirements of BS 7959-2:2000. May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc. Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.	
Fire resistance:	Good. (Physically flame-retardant) Incinerable to zero ash.	
Disposal:	Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.	
Safety data:	Refer to our Safety Data Sheet. This product is non-toxic to users and to aquatic life. Further technical advice is available if required.	
Note:	All weights, dimensions, and other figures quoted are approximate.	

Revision Date 06/08/2018