

Direct Antistatic Socks



Supplied in a variety of pack sizes our anti static oil absorbent socks are manufactured from 100% polypropylene outer and filler.

This high capacity absorbent is ideal for diverting or "pooling" spills.

They are also useful for placing alongside or around machinery, tanks or drums to prevent any leaks spreading across the floor.

Absorb oil only, no waste on water or in rain.

Will not allow liquid to spread

Strong permeable outer skin will not tear.

Suitable for

- Indoor use
- Laboratories
- Process plants
- Households

SKU Code	Sock Size	Pack Quantity	Absorbency Litres Min - Max	Pack weight kgs
502/01022/AW	7.5 dia. x 125cm	10	35 - 40	3.1
502/01024/AW	7.5 dia. x 125cm	40	140 - 160	12.1
502/01025/AW	7.5 dia. x 125cm	20	70 - 80	6.1

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

- Outer casing:** 100% polypropylene spun-bonded
Static Dissipating
Tensile strength (mean): 400N (200mm strip/EN ISO 10319)
UV resistant
- Filler:** Polypropylene and other fibres
- Fitting:** Polypropylene thread tails for joining
- Pack type:** Bag
- Compatibility:** Water-repellency exceeds requirements of BS 7959-2:2000. May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc.

Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.

- Fire resistance:** Good. (Physically flame-retardant)
Incinerable to zero ash.
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed
- Safety data:** This product is non-toxic to users and to aquatic life.
Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date 06/08/2018