

Direct Chemical Pads



Chemical absorbents soak up and hold chemicals, they do not allow a spill to spread. Our chemical absorbent pads, rolls and sock, cushions, loose materials, and booms are 100% polypropylene giving excellent chemical resistance.

Chemical absorbents can be incinerated, reducing costs.

They are a high visible yellow colour.

They can be used around acid baths, chemical reactors, process plants, in laboratories and at chemical storage areas. They absorb acids and alkalis as well as oil, water, and coolants.

Direct Chemical pads should be used for wiping down surfaces, in laboratories to clean up and collect spills, in chemical storage areas, as part of your spill response plan.

They are supplied in plastic packs, suitable for damp areas.

They can be used inside and outside for spill, leaks and drips of corrosive chemicals and hazardous liquids. Suitable for environments where aggressive chemicals have been spilt and need to be contained and cleaned up.

Excellent chemical resistance with instant high absorbing action and retention for rapid and cost-effective spill clean-up.

Coloured for easy identification.

Overlap multiple pads to cover a larger spill area.

Absorbency

r

- Indoor/outdoor use
- Laboratories
- Process plants
- Chemical storage
- Chemical reactors

SKO COUE	Fau weight	Fau Size	Quantity	Litres	weight kgs
502/02001	175gsm	40 x 52cm	200	66 - 131	7.5
502/02002	175gsm	40 x 52cm	50	16 - 33	2.0
502/02002-24	240gsm	40 x 50cm	100	43 - 86	4.8

Dock

Pad size

Sorbency: Lower figure test method to BS 7959-1:2004 using water. Higher figure based on high viscosity liquid with no drain.

Spill Kits Direct is a trading style of Oil Pollution Environmental Control Limited. Company **Reg No**: 146775. **VAT Reg No**: 330 9016 89 Registered in England & Wales – Registered Office: Unit 2A, Follifoot Ridge Business Park, Harrogate, North Yorkshire, HG3 1DP, United Kingdom. **Reservation** as to title: The ownership of the goods shall not pass to the customer until full payment of the purchase price, but the risk shall pass upon delivery. The benefit and/or proceeds of any dealings with goods by the customer in contravention of the above reservation of property rights shall be held in trust for us

SKILCode Pad weight



.



Composition:	 Lightweight pads >99.5% Polypropylene, <0.5% dye Melt blown Mediumweight pads >99.5% Polypropylene, <0.5% dye Melt blown, ultrasonically bonded, spunbonded laminated on one side.
Pack type:	Bag
Compatibility:	May be safely used with all aqueous solutions and liquids immiscible with water, such as hydrocarbons, solvents, mineral oils, <u>with the exception of strong oxidising agents</u> . Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions considered.
Fire resistance:	Good. (Physically flame-retardant) Incinerable to zero ash.
Disposal:	Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, considering the classification of the liquid absorbed.
Safety data:	This product is non-toxic to users and to aquatic life.
	Further technical advice is available if required.
Note:	All weights, dimensions, and other figures quoted are approximate. Revision Date 06/08/2018

