

Direct Kit 14



Available as oil, chemical or maintenance spill kit. Colour coded for easy identification

The principal reason for colour coding is for identifying the type of hazard you are dealing with. The sorbents are also different in manufacture. Whilst oil only sorbents are oleophilic and hydrophobic (absorbs oil/rejects

water) chemical, and maintenance sorbents are hydrophilic (absorb water) which allows the recovery of aqueous based liquids.

Direct Kit 14 is packaged in a heavy duty, UV stabilised waterproof industrial bin with four wheels suitable for all surfaces. Its fully opening lid allows for ease of use.

A large size kit that can be used in:

- hoses blowing during delivery
- tank overfills
- tank roll overs
- catastrophic incidence caused by vandalism or accident
- this large kit can deal with anything.

Contents	Quantity
Pads 40 cm x 52 cm	400
Mini roll 50cm x 42m	2
Roll large	1
Socks 300 cm x 7.5 cm	10
Boom 400cm x 20 cm	4
Cushion 55 cm x 35 cm x 10cm	10
Flow stopper tub (800g)	1
Flow stopper mat	2
Wooden stakes	2
Disposable bag & ties	10

Type	SKU Code	Absorbency litres	Weight	Size
Oil	501/01016	979 - 1225	142.5 Kgs	110 × 135 × 135 cm
Chemical	501/02016	605 – 950	148.0 Kgs	110 × 135 × 135 cm
Maintenance	501/03016	605 - 950	146.1 Kgs	110 × 135 × 135 cm

Replenishment: A full refill kit is available for this product.

Type	SKU Code	Absorbency	Weight	Size
Oil	501/01016/R	979 - 1225	77.9 Kgs	n/a
Chemical	501/02016/R	605 - 950	83.4 Kgs	n/a
Maintenance	501/03016/R	605 - 950	81.5 Kgs	n/a

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

- Instructions for use:** It is important that a suitable and sufficient Risk Assessment is carried out on each incident and correct PPE is worn. Depending on the nature of the spill a combination of the contents of the kit may be used.
- Compatibility:** The absorbents within these kits may be safely used with all aqueous solutions and liquids immiscible with water, such as hydrocarbons, solvents, mineral oils, ***except for strong oxidising agents***. Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions considered. Water-repellency exceeds requirements of BS 7959-2:2000
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, considering the classification of the liquid absorbed.
- Safety Data:** Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018