

## Direct Kit 11



Available as oil, chemical or maintenance spill kit. Colour coded for easy identification

The principal reason for colour coding is for identifying the type of hazard you are dealing with. The sorbents are also different in manufacture. Whilst oil only

sorbents are oleophilic and hydrophobic (absorbs oil/rejects water) chemical, and maintenance sorbents are hydrophilic (absorb water) which allows the recovery of aqueous based liquids.

Direct Kit 11 is packaged in a robust lightweight mobile container with

four casters. The lid is completely removable providing easy access to the absorbents inside.

A medium size kit that can be used in lubricant dispensing areas, loading bays, flammable stores, oil drum stores or central emergency response storage areas.

Contents	Quantity
Pads 40 cm x 52 cm	200
Socks 125 cm x 7.5 cm	10
Socks 300 cm x 7.5 cm	5
Cushion 55 cm x 35 cm x 10cm	6
Boom 300cm x 12.5 cm	2
Flow stopper tub (800g)	1
Disposable bag & tie	20

Type	SKU Code	Absorbency	Weight
Oil	501/01011	368 - 443 litres	52.2 Kgs
Chemical	501/02011	230 - 343 litres	54.8 Kgs
Maintenance	501/03011	230 - 343 litres	54.9 Kgs

**Replenishment:** A full refill kit is available for this product.

Type	SKU Code	Absorbency	Weight
Oil	501/01011/R	368 - 443 litres	26.9 Kgs
Chemical	501/02011/R	230 - 343 litres	29.5 Kgs
Maintenance	501/03011/R	230 - 343 litres	29.6 Kgs

*Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain*

- Instructions for use:** It is important that a suitable and sufficient Risk Assessment is carried out on each incident and correct PPE is worn. Depending on the nature of the spill a combination of the contents of the kit may be used.
- Compatibility:** The absorbents within these kits may be safely used with all aqueous solutions and liquids immiscible with water, such as hydrocarbons, solvents, mineral oils, **except for strong oxidising agents**. Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions considered. Water-repellency exceeds requirements of BS 7959-2:2000
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, considering the classification of the liquid absorbed.
- Safety Data:** Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018