

Direct Kit 12



Available as oil, chemical or maintenance spill kit. Colour coded for easy identification

The principal reason for colour coding is for identifying the type of hazard you are dealing with. The sorbents are also different in manufacture. Whilst oil only sorbents are oleophilic and hydrophobic (absorbs oil/rejects

water) chemical, and maintenance sorbents are hydrophilic (absorb water) which allows the recovery of aqueous based liquids.

Direct Kit 12 is packaged in a heavy duty, UV stabilised waterproof container on four wheels. A fully opening lid allows for ease of use.

A large size kit that can be used in:-

- a bulk fuel storage
- waste oil collection points
- fuel delivery points
- near high-risk areas such as rivers and canals.

Due to its size, shape, and portability this is an ideal spill kit for internal use and anywhere where volumes of liquids are stored, delivered, or received.

Contents	Quantity
Pads 40 cm x 52 cm	100
Socks 125 cm x 7.5 cm	12
Boom 400cm x 20 cm	2
Cushion 55 cm x 35 cm x 10cm	12
Loose absorbent 4kg	1
Flow stopper tub (800g)	1
Flow stopper mat	1
Wooden stakes	2
Disposable bag & ties	12

Type	SKU Code	Absorbency	Weight
Oil	501/01014	557 - 658 litres	86.2 Kgs
Chemical	501/02014	301 - 482 litres	91.3 Kgs
Maintenance	501/03014	301 - 482 litres	91.4 Kgs

Replenishment: A full refill kit is available for this product.

Type	SKU Code	Absorbency	Weight
Oil	501/01014/R	557 - 658 litres	46.6 Kgs
Chemical	501/02014/R	301 - 482 litres	51.8 Kgs
Maintenance	501/03014/R	301 - 482 litres	51.8 Kgs

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

- Instructions for use:** It is important that a suitable and sufficient Risk Assessment is carried out on each incident and correct PPE is worn. Depending on the nature of the spill a combination of the contents of the kit may be used.
- Compatibility:** The absorbents within these kits may be safely used with all aqueous solutions and liquids immiscible with water, such as hydrocarbons, solvents, mineral oils, **except for strong oxidising agents**. Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions considered. Water-repellency exceeds requirements of BS 7959-2:2000
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, considering the classification of the liquid absorbed.
- Safety Data:** Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018