

Direct Kit 13



Available as oil, chemical or maintenance spill kit. Colour coded for easy identification

The principal reason for colour coding is for identifying the type of hazard you are dealing with. The sorbents are also different in manufacture. Whilst oil only sorbents are oleophilic and hydrophobic (absorbs oil/rejects

water) chemical, and maintenance sorbents are hydrophilic (absorb water) which allows the recovery of aqueous based liquids.

Direct Kit 13 is packaged in a heavy duty, UV stabilised waterproof bunker with forklift access. Optional heavy-duty wheels are available upon request. Its fully opening lid allows for ease of use.

A large size kit that can be used in: -

- hoses blowing during delivery
- tank overfills
- tank roll overs
- catastrophic incidence caused by vandalism or accident
- this large kit can deal with anything.

Contents	Quantity
Pads 40 cm x 52 cm	200
Mini roll 50cm x 42m	2
Socks 125 cm x 7.5 cm	10
Socks 300 cm x 7.5 cm	4
Boom 400cm x 20 cm	2
Cushion 55 cm x 35 cm x 10cm	10
Flow stopper tub (800g)	1
Flow stopper mat	1
Wooden stakes	2
Disposable bag & ties	10

Type	SKU Code	Absorbency	Weight
Oil	501/01015	794 - 948 litres	124.3 Kgs
Chemical	501/02015	458 - 712 litres	132.6 Kgs
Maintenance	501/03015	458 - 172 litres	130.9 Kgs

Replenishment: A full refill kit is available for this product.

Type	SKU Code	Absorbency	Weight
Oil	501/01015/R	794 - 948 litres	62.8 Kgs
Chemical	501/02015/R	458 - 712 litres	71.0 Kgs
Maintenance	501/03015/R	458 - 172 litres	69.3 Kgs

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

- Instructions for use:** It is important that a suitable and sufficient Risk Assessment is carried out on each incident and correct PPE is worn. Depending on the nature of the spill a combination of the contents of the kit may be used.
- Compatibility:** The absorbents within these kits may be safely used with all aqueous solutions and liquids immiscible with water, such as hydrocarbons, solvents, mineral oils, **except for strong oxidising agents**. Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions considered. Water-repellency exceeds requirements of BS 7959-2:2000
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, considering the classification of the liquid absorbed.
- Safety Data:** Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018