

Direct Kit 120



Available as oil, chemical or maintenance spill kit. Colour coded for easy identification

The principal reason for colour coding is for identifying the type of hazard you are dealing with. The sorbents are also different in manufacture. Whilst oil only sorbents are oleophilic and

hydrophobic (absorbs oil/rejects water) chemical, and maintenance sorbents are hydrophilic (absorb water) which allows the recovery of aqueous based liquids.

Direct kit 120 is packaged in a robust UV stabilised waterproof 120 litre wheeled bin.

A medium kit that can be used inside or outside. Ideal for cars for first response teams or outside in high-risk areas such as storage and transfer yards.

Ideal for fast response to medium spills with high absorbency.

Contents	Quantity
Pads 40 cm x 52 cm	50
Socks 125 cm x 7.5 cm	5
Socks 300 cm x 7.5 cm	2
Cushion 55 cm x 35 cm x 10cm	3
Disposable bag and ties	4
Heavy duty wheeled bin 120L	1

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

Type	SKU Code	Absorbency	Weight
Oil	501/01005	112-134 litres	18.8 Kgs
Chemical	501/02005	68 - 104 litres	19 Kgs
Maintenance	501/03005	68 - 104 litres	18.7 Kgs

Replenishment: A full refill kit is available for this product.

Type	SKU Code	Absorbency	Weight
Oil	501/01005/R	112-134 litres	4.3 Kgs
Chemical	501/02005/R	68-104 litres	4.3 Kgs
Maintenance	501/03005/R	68-104 litres	4.4 Kgs

- Instructions for use:** It is important that a suitable and sufficient Risk Assessment is carried out on each incident and correct PPE is worn. Depending on the nature of the spill a combination of the contents of the kit may be used.
- Compatibility:** The absorbents within these kits may be safely used with all aqueous solutions and liquids immiscible with water, such as hydrocarbons, solvents, mineral oils, **except for strong oxidising agents**. Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions considered. Water-repellency exceeds requirements of BS 7959-2:2000
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, considering the classification of the liquid absorbed.
- Safety Data:** Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018